



## STEGOTACK™ TAPE

A STEGO INDUSTRIES, LLC INNOVATION

### 1. PRODUCT NAME

STEGOTACK TAPE

### 2. SUPPLIER

ramsetreid  
 1 Ramset Drive  
 Chirnside Park  
 Victoria 3116  
 Australia  
 1300 DANLEY (1300 326 539)  
 sales@danley.com.au  
 www.danley.com.au



### 3. PRODUCT DESCRIPTION

**USES:** StegoTack Tape is a double-sided adhesive strip used to bond and seal Stego™ Wrap Vapour Barrier to concrete, masonry, wood, metal, and other surfaces. StegoTack Tape is a flexible and mouldable material to allow for a variety of applications and installations.

**COMPOSITION:** StegoTack Tape is made from a blend of synthetic rubber and resins.

**SIZE:** StegoTack Tape is 51 mm (2") x 15 m (50'). StegoTack Tape ships 12 rolls in a case.

### 4. TECHNICAL DATA

**TABLE 4.1: PHYSICAL PROPERTIES OF STEGOTACK TAPE**

PROPERTY	RESULTS
Dimensions	51 mm (2") x 15 m (50')
Total Thickness	0.76 mm (30 mil)
Permeance (at 0.76 mm/30 mil)	1.7 ng/(m <sup>2</sup> *s*Pa) (0.03 gr/(ft <sup>2</sup> *hr*in-Hg)
Colour	Grey
Material	Synthetic rubber blend
Adhesion to Steel	2.19 kN/m (12.5 lb/in) width ASTM D1000
Installation Temperature	4°C/43°C (40°F/110°F)
In Service Temperature Range	-29°C/60°C (-20°F/+140°F)
VOC Content	No VOCs, 100% solids

### 5. INSTALLATION

**TO WALLS:** Make sure the area of adhesion is free of dust, dirt, debris, moisture, and frost to allow maximum adhesion. Remove release liner on one side and stick to desired surface. When ready to apply Stego Wrap, remove the exposed release liner and press Stego Wrap firmly against StegoTack Tape to secure.

Cut StegoTack Tape using a utility knife or scissors. Cut StegoTack Tape before removing the release liner for easier cutting. Install StegoTack Tape between 4°C and 43°C. For additional information please refer to Stego's complete installation instructions.